


NEW
DOWNLIGHT
ELIO

INCASSO



	A mm	mm	g
6 W	Ø 101	Ø 72	40
9 W	Ø 116	Ø 87	55
12 W	Ø 132	Ø 105	70
15 W	Ø 151	Ø 122	95
18 W	Ø 176	Ø 147	120
24 W	Ø 201	Ø 172	215

	SOURCE	OUTPUT			
6 W	540 lm	390 lm	3000K	ELO-060730 NEW	4,95 €
			4000K	ELO-060740 NEW	
9 W	820 lm	580 lm	3000K	ELO-090930 NEW	5,95 €
			4000K	ELO-090940 NEW	
12 W	1.160 lm	840 lm	3000K	ELO-121130 NEW	6,85 €
			4000K	ELO-121140 NEW	
15 W	1.490 lm	1.080 lm	3000K	ELO-151230 NEW	8,95 €
			4000K	ELO-151240 NEW	
18 W	1.830 lm	1.260 lm	3000K	ELO-181530 NEW	11,95 €
			4000K	ELO-181540 NEW	
24 W	2.490 lm	1.730 lm	3000K	ELO-241730 NEW	14,95 €
			4000K	ELO-241740 NEW	



Apparecchio a incasso LED. Illuminazione diffusa e omogenea, diffusore in PC, corpo in PP. Per uso interno.

LED recessed luminaire. Diffused and homogeneous lighting, PC diffuser, PP body. For indoor use.

COMPLIANCE

EMC DIRECTIVE 2014/30/EU | EN 55015:2013 /A1:2015 | EN 61547:2009 | EN 61000 3-2:2014 | EN 61000 3-3:2013
LVD DIRECTIVE 2014/35/EU | EN 60598-1:2015+A1:2018 | EN 60598 2-2:2012 | EN 62471:2008 | EN 62493:2015
ROHS DIRECTIVE 2011/65/CE | IEC6231-5:2013 | IEC62321-7-1:2015 | IEC62321-7-2:2017 | IEC623 21-4:2017 | IEC62321-6:2015 | IEC 62321-8:2017