



PAVI-078930




PAVI-1216030


CALPESTABILE

PAVI


IP67 - 1-2-4 LIGHT



SOURCE		OUTPUT			
1 W	120 lm	80 lm	3000 K	PAVI-014230	38,00 €
			4000 K	PAVI-014240	



SOURCE		OUTPUT			
3 W	300 lm	250 lm	3000 K	PAVI-038930	74,50 €
			4000 K	PAVI-038940	
7 W	660 lm	420 lm	3000 K	PAVI-078930	77,00 €
			4000 K	PAVI-078940	



SOURCE		OUTPUT			
12 W	1.150 lm	840 lm	3000 K	PAVI-1216030	125,00 €
			4000 K	PAVI-1216040	



Incasso tondo calpestabile per installazione a pavimento. Anello e corpo in alluminio, vetro temperato, cavo in neoprene. Resistenza a pressione di 500 Kg.

Walkable round recessed light for floor installation. Aluminum ring and body, tempered glass, neoprene cable. Pressure resistance of 500 Kg.

INCLUDED



CONTROCASSA IN POLICARBONATO
POLYCARBONATE CASING

OPTIONAL PAG. 245

ALIMENTATORI E CONNETTORI
POWER SUPPLIES AND CONNECTORS

OUTDOOR