



PAVI2L-087030




PAVIC4L-0513030

CALPESTABILE

# PAVI

IP67 - 1-2-4 LIGHT

## SUPERFICIE SURFACE




### OUTPUT

0,4 W	8 lm	1 Luce Light	3000 K	<b>PAVI1L-047030</b>	20,50 €
			4000 K	<b>PAVI1L-047040</b>	
0,8 W	16 lm	2 Luci Lights	3000 K	<b>PAVI2L-087030</b>	24,00 €
			4000 K	<b>PAVI2L-087040</b>	



## INCASSO RECESSED



### SOURCE

### OUTPUT

5 W	384 lm	160 lm	2 Luci Lights	3000 K	<b>PAVIC2L-0513030</b>	74,50 €
			4 Luci Lights	3000 K	<b>PAVIC4L-0513030</b>	
4 W	300 lm	125 lm	4 Luci Lights	4000 K	<b>PAVIC4L-0513040</b>	



INCLUDED



CONTROCASSA IN POLICARBONATO  
POLYCARBONATE CASING

OUTDOOR

## TECHNICAL NOTES



1, 2 O 4 LUCI CON ANGOLO DI 100°  
1, 2 OR 4 LIGHTS WITH 100 ° ANGLE

OPTIONAL PAG. 245

ALIMENTATORI E CONNETTORI  
POWER SUPPLIES AND CONNECTORS

Calpestabile luce radente a superficie o a incasso per installazione a pavimento. Corpo in alluminio, cavo in neoprene. Resistenza a pressione di 500 Kg.

Walkable surface or recessed glancing light for floor installation. Aluminum body, neoprene cable. Maximum resistance to pressure of 500 Kg.