



PAVI2L-087030




PAVIC4L-0513030

CALPESTABILE

PAVI

IP67 - 1-2-4 LIGHT

SUPERFICIE SURFACE



OUTPUT


0,4 W	8 lm	1 Luce Light	3000 K	PAVI1L-047030	20,50 €
			4000 K	PAVI1L-047040	
0,8 W	16 lm	2 Luci Lights	3000 K	PAVI2L-087030	24,00 €
			4000 K	PAVI2L-087040	



24 V IP67 IK06 100°



INCASSO RECESSED



SOURCE

OUTPUT

5 W	384 lm	160 lm	2 Luci Lights	3000 K	PAVIC2L-0513030	74,50 €
			4 Luci Lights	3000 K	PAVIC4L-0513030	
4 W	300 lm	125 lm	4 Luci Lights	4000 K	PAVIC4L-0513040	



24 V IP67 IK06 100°



INCLUDED



CONTROCASSA IN POLICARBONATO
POLYCARBONATE CASING

OUTDOOR

TECHNICAL NOTES



1, 2 O 4 LUCI CON ANGOLO DI 100°
1, 2 OR 4 LIGHTS WITH 100 ° ANGLE

OPTIONAL PAG. 245

ALIMENTATORI E CONNETTORI
POWER SUPPLIES AND CONNECTORS

Calpestabile luce radente a superficie o a incasso per installazione a pavimento. Corpo in alluminio, cavo in neoprene. Resistenza a pressione di 500 Kg.

Walkable surface or recessed glancing light for floor installation. Aluminum body, neoprene cable. Maximum resistance to pressure of 500 Kg.