


P-QUADRO
ADVANCE


P-QUADRO
ADVANCE

30 X 60



SOURCE		OUTPUT		PRICE
24 W	2.700 lm	1.700 lm	3000K	
			4000K	PQA-243040


30 X 120



SOURCE		OUTPUT		PRICE		
38 W	4.300 lm	3.900 lm	CRI 80		3000K	PQA-421230
				4000K	PQA-421240	
38 W	4.300 lm	3.900 lm	CRI 90	3000K	PQA90-421230	69,50 €
				4000K	PQA90-421240	

SOURCE		OUTPUT		PRICE		
38 W	4.300 lm	3.900 lm	CRI 80		4000K	PQAN-421240
			CRI 90	4000K	PQAN90-421240	56,50 €

60 X 120



SOURCE		OUTPUT		PRICE	
64 W	9.000 lm	7.900 lm	4000K		PQA-646040

OPTIONAL PAG. 44-47

ALIMENTATORI E ACCESSORI
POWER SUPPLIES AND ACCESSORIES

COMPLIANCE

Pannelli dal design elegante e ultra sottili. Disponibili in diverse temperature di colore, con alimentatore incluso o opzionale. Assenza di raggi UV e IR, antisfarfallio.

Ultra thin panels with elegant design. Available in different color temperatures, included or optional power supply. no UV and IR rays, flicker-free.

EMC DIRECTIVE 2014/30/EU | EN 55015:2013/A1:2015 | EN 61547:2009 | EN 61000 3-2:2014 | EN 61000 3-3:2013
LVD DIRECTIVE 2014/35/EU | EN 60598-1:2015+A1:2018 | EN 60598 2-2:2012 | EN 62471:2008 | EN 62493:2015
ROHS DIRECTIVE 2011/65/CE | IEC 6231-5:2013 | IEC 62321-7-1:2015 | IEC 62321-7-2:2017 | IEC 62321-4:2017 | IEC 62321-6:2015 | IEC 62321-8:2017