




P-QUADRO  
**RECESSED**


P-QUADRO  
**RECESSED**

62 X 62




SOURCE		OUTPUT		61,00 €
42 W	4.600 lm	3.700 lm	3000K	
			4000K	<b>PQR-406240</b>

60 X 10



OUTPUT		35,00 €
18 W	700 lm	
		4000K

120 X 10



OUTPUT		54,00 €
36 W	1.476 lm	
		4000K

FOCUS

Cornice invisibile, solo 1 mm di spessore  
Invisible frame, only 1 mm thickness

INCLUDED



CLIP PER INSTALLAZIONE A SCOMPARSA  
CLIP FOR CONCEALED INSTALLATION

OPTIONAL PAG. 44-47

ALIMENTATORI E ACCESSORI  
POWER SUPPLIES AND ACCESSORIES

COMPLIANCE

Pannello LED con design innovativo e effetto a scomparsa, per applicazioni in cartongesso. Cornice ultrasottile di solo 1 mm di spessore. Alimentatore esterno in dotazione, privo di raggi UV e IR.

LED panel with innovative design and concealed effect, for plaster-board applications. Ultra-thin frame, only 1 mm thickness. External power supply included. UV and IR rays free.

EMC DIRECTIVE 2014/30/EU | EN 55015:2013+A1:2015 | EN 61547:2009 | EN 61000 3-2:2014 | EN 61000 3-3:2013

LVD DIRECTIVE 2014/35/EU | EN 60598-1:2015+A1:2018 | EN 60598 2-2:2012 | EN 62471:2008 | EN 62493:2015

ROHS DIRECTIVE 2011/65/CE | IEC 6231-5:2013 | IEC 62321-7-1:2015 | IEC 62321-7-2:2017 | IEC 62321-4:2017 | IEC 62321-6:2015 | IEC 62321-8:2017