






# DOWNLIGHT SPOTFIVE

TRICOLOR - DIMMABLE



|      | A<br>mm | B<br>mm | Ø<br>mm | g   |
|------|---------|---------|---------|-----|
| 9 W  | Ø113    | 59      | Ø92     | 130 |
| 14 W | Ø145    | 66      | Ø130    | 185 |
| 17 W | Ø174    | 69      | Ø150    | 252 |
| 25 W | Ø244    | 85      | Ø205    | 381 |


|      | SOURCE   | OUTPUT   |                       |                    |
|------|----------|----------|-----------------------|--------------------|
| 9 W  | 960 lm   | 800 lm   | 3000K - 4000K - 6500K | SPF-091100 19,00 € |
| 14 W | 1.510 lm | 1.260 lm | 3000K - 4000K - 6500K | SPF-141400 26,50 € |
| 17 W | 1.600 lm | 1.550 lm | 3000K - 4000K - 6500K | SPF-171700 35,00 € |
| 25 W | 2.900 lm | 2.450 lm | 3000K - 4000K - 6500K | SPF-252400 48,00 € |



CONICAL DIAGRAM

Illuminance (lx)

|     | 9 W  | 14 W  | 17 W  | 25 W  |
|-----|------|-------|-------|-------|
| 2 m | 85,2 | 162,1 | 181,7 | 266,3 |
| 3 m | 42,4 | 71,9  | 80,7  | 118,3 |
| 4 m | 22,5 | 40,5  | 45,4  | 66,5  |
| 5 m | 12,5 | 25,9  | 29,1  | 42,6  |



TECHNICAL NOTES



DIMMERABILE CON SISTEMI A TAGLIO DI FASE  
DIMMABLE WITH TRAILING-EDGE SYSTEMS



REGOLAZIONE DEL COLORE LUCE TRAMITE SELETTORE SUL RETRO  
COLOR TEMPERATURE ADJUSTMENT THROUGH SELECTOR ON THE BACK

COMPLIANCE

Downlight dimmerabile con sistemi trailing-edge o Led Dimmer e con selettore CCT per la regolazione del colore luce.

Dimmable downlight with trailing-edge or Led Dimmer systems and with CCT selector for adjusting the color temperature.

EMC DIRECTIVE 2014/30/EU | EN 55015:2013 /A1:2015 | EN 61547:2009 | EN 61000 3-2:2014 | EN 61000 3-3:2013  
LVD DIRECTIVE 2014/35/EU | EN 60598-1:2015+A1:2018 | EN 60598 2-2:2012 | EN 62471:2008 | EN 62493:2015  
ROHS DIRECTIVE 2011/65/CE | IEC6231-5:2013 | IEC62321-7-1:2015 | IEC62321-7-2:2017 | IEC623 21-4:2017 | IEC62321-6:2015 | IEC 62321-8:2017