PROIETTORE

SIRIO SLIM

PROIETTORI

SIRIO SLIM

IP66 - ULTRA SLIM

IK08 IP66



	A mm	B mm	C mm	g
20 W	160	147	29	480
30 W	160	147	29	480
50 W	200	178	29	760
70 W	270	230	29	1400
100 W	270	230	29	1400
150 W	366	303	34	2800
200 W	366	303	34	2800

	OUTPUT					
20 W	2.100 lm	Grey	4000 K	SRS-209540	1/24	27,50 €
			6000 K	SRS-209560		
		White	4000 K	SRSB-209540		
30 W	3.150 lm	Grey	4000 K	SRS-309540	1/24	32,50 €
			6000 K	SRS-309560		
		White	4000 K	SRSB-309540		
50 W	5.250 lm	Grey	4000 K	SRS-509540	1/20	36,00 €
			6000 K	SRS-509560		
		White	4000 K	SRSB-509540		
70 W	7.350 lm	Grey	4000 K	SRS-709540	1/12	65,00 €
			6000 K	SRS-709560		
		White	4000 K	SRSB-709540		
100 W	10.500 lm	Grey	4000 K	SRS-1009540	1/12	89,00 €
			6000 K	SRS-1009560		
		White	4000 K	SRSB-1009540		
150 W	15.750 lm	Grey	4000 K	SRS-1509540	1/6	135,00 €
			6000 K	SRS-1509560		
		White	4000 K	SRSB-1509540		
200 W	21.000 m	Grey	4000 K	SRS-2009540	1/6	152,00 €
			6000 K	SRS-2009560		
		White	4000 K	SRSB-2009540		

200-240 V IP66 IK08 110°

HIGH DISSIPATION ULTRASLIM 304 STAINLESS STEEL

DIE-CAST ALUMINUM GLASS 30.000 h 4000 K 35.000 h 6000 K

Proiettore ultraslim IP66 con un design sottile e resistente all'acqua, ideale per l'uso all'aperto. Realizzato in alluminio pressofuso e diffusore in vetro ad alta resistenza.

IP66 ultra-slim floodlight with a slim, water-resistant design, ideal for outdoor use. Made of die-cast aluminum and high resistance glass diffuser.

TECHNICAL NOTES

VALVOLA ANTI CONDENSA IMPERMEABILE. RIMUOVE L'UMIDITÀ ED EVITA LA CONDENSA
WATERPROOF ANTI-CONDENSATION VALVE. REMOVES MOISTURE AND PREVENTS CONDENSATION

CAVO IN GOMMA H05RN-F 3 X 1.0 MM² RESISTENTE AI RAGGI UV E ALLE BASSE TEMPERATURE. PRESSACAVO IN ACCIAIO INOX.
RUBBER CABLE H05RN-F 3X1.0 MM² RESISTANT TO UV RAYS AND LOW TEMPERATURES. STAINLESS STEEL CABLE GLAND.