


# DOWNLIGHT ZENO

TRICOLOR

INCASSO

## ROUND




	A mm	mm	g
10 W	Ø90	Ø70	160
16 W	Ø140	Ø120	268
32 W	Ø220	Ø200	460

SOURCE		OUTPUT					
10 W	1.000 lm	750 lm	∠ 90°	3000K - 4000K - 6500K	<b>ZNR-1070</b>	14,00 €	
16 W	1.500 lm	1.300 lm	∠ 100°	3000K - 4000K - 6500K	<b>ZNR-16120</b>	22,00 €	
32 W	4.200 lm	3.500 lm	∠ 105°	3000K - 4000K - 6500K	<b>ZNR-32200</b>	38,00 €	



## SQUARE



	A mm	mm	g
10 W	90	70 x 70	170
16 W	140	120 x 120	313
32 W	223	208 x 208	566

SOURCE		OUTPUT					
10 W	1.000 lm	750 lm	∠ 90°	3000K - 4000K - 6500K	<b>ZNS-1070</b>	17,00 €	
16 W	1.500 lm	1.300 lm	∠ 100°	3000K - 4000K - 6500K	<b>ZNS-16120</b>	26,00 €	
32 W	4.200 lm	3.500 lm	∠ 105°	3000K - 4000K - 6500K	<b>ZNS-32200</b>	43,00 €	




## OPTIONAL

RICAMBIO DRIVER  
SPARE DRIVER 

10 W	<b>RDZN-10</b> <span style="color: red;">NEW</span>	11,00 €
16 W	<b>RDZN-16</b> <span style="color: red;">NEW</span>	11,00 €
32 W	<b>RDZN-32</b> <span style="color: red;">NEW</span>	12,00 €

## TECHNICAL NOTES



REGOLAZIONE DEL COLORE LUCE TRAMITE SELETTORE  
COLOR TEMPERATURE ADJUSTMENT THROUGH SWITCH

## COMPLIANCE

Downlight LED di facile installazione grazie alle pratiche clip a molla. Permette la regolazione del colore luce tramite selettore.

Easy to install LED downlight thanks to practical spring clips. Allows adjustment of the light color using a selector.

EMC DIRECTIVE 2014/30/EU | EN 55015:2013 /A1:2015 | EN 61547:2009 | EN 61000 3-2:2014 | EN 61000 3-3:2013  
LVD DIRECTIVE 2014/35/EU | EN 60598-1:2015+A1:2018 | EN 60598 2-2:2012 | EN 62471:2008 | EN 62493:2015  
ROHS DIRECTIVE 2011/65/CE | IEC6231-5:2013 | IEC62321-7-1:2015 | IEC62321-7-2:2017 | IEC623 21-4:2017 | IEC62321-6:2015 | IEC 62321-8:2017