

NEW

LAMPIONE URBANO
ZEUS



150 W


40 W

NEW

LAMPIONE URBANO

ZEUS

CLASS II - 186 lm/W - IP65 - ASYMMETRICAL




| | A mm | B mm | g g |
|-------|---------|---------|--------|
| 40 W | 210 | 505 | 2480 |
| 60 W | 210 | 505 | 2426 |
| 90 W | 240 | 540 | 2907 |
| 150 W | 280 | 610 | 4218 |

| | SOURCE | OUTPUT | | |
|-------|-----------|-----------|--------|-----------------------|
| 40 W | 7.450 lm | 6.800 lm | 3000 K | ZS-4017030 NEW |
| | | | 4000 K | ZS-4017040 NEW |
| 60 W | 11.180 lm | 10.280 lm | 3000 K | ZS-6017030 |
| | | | 4000 K | ZS-6017040 |
| 90 W | 16.880 lm | 15.300 lm | 3000 K | ZS-9017030 |
| | | | 4000 K | ZS-9017040 |
| 150 W | 27.840 lm | 25.610lm | 3000 K | ZS-15017030 |
| | | | 4000 K | ZS-15017040 |

 100-277 V
  IP65
  IK08
  70° x 150°
  186 lm/W
  RAL 9007
  Ø 60 mm
  DIE-CAST ALUMINIUM
  TEMPERED GLASS
 100.000 h
 5 YEARS
 

POLAR DIAGRAM



Illuminazione stradale di classe 2 in alluminio pressofuso di alta qualità, montabile su palo dritto o curvo. Dotato di scaricatore integrato da 10 kV per proteggere il prodotto da cariche elettrostatiche e sovratensioni. Lenti asimmetriche per una distribuzione efficiente della luce lungo la strada. Verniciatura a polveri epossidiche per maggiore resistenza agli agenti corrosivi. Soluzione affidabile e durevole per garantire sicurezza e visibilità in ambienti urbani e suburbani.

Class 2 street light made of high quality die-cast aluminium, mountable on straight or curved pole. Equipped with integrated 10 kV arrester to protect the product from electrostatic charges and overvoltages. Asymmetrical lenses for efficient distribution of light along the road. Epoxy powder coating for greater resistance to corrosive agents. Reliable and durable solution to ensure safety and visibility in urban and suburban environments.

TECHNICAL NOTES



FACILE REGOLAZIONE ±15° CON TACCHE DI BLOCCAGGIO
EASY ADJUSTMENT WITH ± 15° LOCKING NOTCHES

INSTALLATION



IDONEO PER FISSAGGIO A PALO DRITTO O CURVO
SUITABLE FOR CURVED OR STRAIGHT POLE

INCLUDED



SCARICATORE DI SOVRATENSIONE DA 10 KV INTEGRATO: EVITA IL DANNEGGIAMENTO DEL PRODOTTO IN CASO DI FORTI CARICHE ELETTROSTATICHE O SOVRATENSIONI
 INTEGRATED 10 KV SPD (SURGE PROTECTION DEVICE): AVOID DAMAGE TO THE PRODUCT IN THE EVENT OF STRONG ELECTROSTATIC CHARGES OR OVERVOLTAGES

COMPLIANCE

EMC DIRECTIVE 2014/30/EU | EN 55015:2019 | EN 61547:2009 | EN 61000-3-2:2019 | EN 61000-3-3:2013+A1:2019
 LVD DIRECTIVE 2014/35/EU | EN-60598-1:2015+A1:2018 | EN 62493:2015 | EN-60598-2-3:2003+A1:2011
 ROHS DIRECTIVE 2011/65/CE | IEC 62321-1:2013 | IEC 62321-2:2013 | IEC 62321-3-1:2013 | IEC6231-4:2013+A1:2017
 IEC6231-5:2013 | IEC62321-6:2015 | IEC62321-7-1:2015 | IEC62321-7-2:2017 | IEC62321-8:2017

TECHNICAL INDOOR

INDOOR

INDUSTRIAL

TECHNICAL OUTDOOR

OUTDOOR

SOLAR

WORK

SORGENTI